

I claim:

- Sub B1*
1. A barrel assembly for a weapon, said barrel assembly including:
 - a ¹²barrel;
 - 5 a plurality of ¹⁴projectile assemblies axially disposed in end to end abutting relationship within said barrel for operative sealing engagement with the bore of the barrel, each projectile including a ²⁶projectile head and an integral ²⁵cylindrical spacer portion extending axially and rearwardly from said projectile head;
 - 10 ¹⁶discrete propellant charges accommodated within said cylindrical spacer portion for propelling respective projectile assemblies sequentially through the muzzle of the barrel;
 - ¹⁹ignition means for igniting said discrete propellant charges; and
 - ²⁰control means for selectively and sequentially actuating the ignition means.
 - 15 2. The barrel assembly as claimed in Claim 1 wherein a ²⁹rearward end of the cylindrical spacer portion is adapted to abut the forward or leading end of the subsequent projectile assembly.
 3. The barrel assembly as claimed in Claim 1 wherein the cylindrical spacer portion
 - 20 is expandable into operative sealing contact with said bore of the barrel.
 - Sub B2*
 - 25 4. The barrel assembly as claimed in Claim 3 wherein the interior of the cylindrical spacer portion is ²⁷structurally reinforced to prevent excessive radial expansion of the projectile.
 5. A barrel assembly for a weapon, said barrel assembly including:
 - a barrel having a muzzle;
 - 30 a plurality of projectiles axially disposed in end to end abutting relationship within said barrel, each projectile including a projectile head and a trailing cylindrical extension in close proximity with the barrel;
 - an internal wedging surface, at or adjacent the trailing end of said cylindrical extension which accommodates a tapered nose part of the following projectile, for

10006532 120501

17

expanding said trailing end into enhanced sealing engagement with the barrel upon engagement of said wedging surface with said tapered nose part;

discrete propellant charges for propelling respective projectiles sequentially through the muzzle of said barrel;

ignition means disposed ¹⁸externally of the barrel for igniting said discrete propellant charges; and

control means for selectively and sequentially actuating said ignition means.

6. The barrel assembly as claimed in Claim 5 wherein said trailing cylindrical extension at least partly defines a propellant space therein.

Sub B3
7. The barrel assembly as claimed in either Claim 5 or Claim 6 wherein ¹⁹propellant charges surround the noses of respective following projectiles externally of the trailing cylindrical extension.

NE
8. The barrel assembly as claimed in Claim 5 wherein each projectile assembly includes an internal spacer which extends through the trailing cylindrical extension from the projectile head to abut or cooperate with the inserted projectile head of a following projectile, whereby axial compressive loads applied to a stack of abutting projectiles arranged in sealing engagement within the barrel may be resisted.

NE
9. The barrel assembly as claimed in Claim 5 wherein axial compressive loads applied to a stack of abutting projectiles arranged in sealing engagement within the barrel may be distributed back to said barrel from individual projectiles through their engagement with the barrel.

10. The barrel assembly as claimed in claim 5 wherein the trailing cylindrical extension is ²⁰[a (thin) cylindrical rear extension] of the projectile head.

NE
11. The barrel assembly as claimed in Claim 8 wherein the internal spacer includes support members for the trailing cylindrical extension.

10006537-12501

18

12. ^{NE} The barrel assembly as claimed in either Claim 8 or Claim 11 wherein the internal spacer is integral with the head and trailing cylindrical extension.

13. ^{NE} The barrel assembly as claimed in either Claim 8 or Claim 11 wherein the internal spacer is formed separately from the head and trailing cylindrical extension.

14. ^{NE} The barrel assembly as claimed in Claim 8 wherein, upon loading respective projectiles into the barrel and thereafter causing an axial displacement of the projectiles causes radial expansion of said trailing ends thereof to enhance the sealing engagement between the projectiles and the barrel.

15. ^{NE} The barrel assembly as claimed in Claim 14 wherein the axial displacement is suitably caused to said projectiles individually, subsequent to each projectile being loaded into the barrel.

16. ^{NE} The barrel assembly as claimed in either Claim 14 or Claim 15 wherein the radial expansion into enhanced sealing engagement with the barrel is limited through engagement between the penetrating nose of a following projectile and the internal spacer.

100065333 100504